























TYPE: Ranger
MODEL: PX / T7 MK3
YEAR: Mid 06/2018 on
DETAIL: 4x4 Strut Mounted Front Bump Stop Models Only,
Also Suits 4x2 Highrider
 Australian and Internationally delivered models
 with Bolt and Eye Lower Front Strut Bush



FRONT			QTY	PART NUMBER	PRICE	REAR			QTY	PART NUMBER	PRICE
COIL SPRING						LEAF SPRING					
	Linear Rate Standard Height (10mm Lift) 40-70Kg	1	C19-508	B			3 + 3 Leaves Medium Duty Raised Height (35mm Lift) Up to 100Kg Constant Load	2	L19-131-R		
	Linear Rate Raised Height (45mm Lift)	1	C19-510	B			4 + 3 Leaves Heavy Duty Raised Height (40mm Lift) 280Kg Constant Load (Recommended)	2	L19-132-R		
	Linear Rate Raised Height (45mm Lift) 40-70Kg	1	C19-512	B			5 + 3 Leaves Super Heavy Duty Raised Height (40mm Lift) 500Kg Constant Load	2	L19-133-R		
	Linear Rate Raised Height (45mm Lift) 80-100Kg	1	C19-514	B			3 + 1 Leaves (Parabolic) Raised Height (50mm Lift) 150Kg Constant Load Comfort Option	2	L19-135-RP		
							3 + 1 Leaves (Parabolic) Raised Height (60mm Lift)	2	L19-135-RP		
SHOCK ABSORBER						SHOCK ABSORBER					
Must Fit Sway Bar Link SE19-570 With These Shock Absorbers											
	Twin Tube Nitro-Gas	2	GS19-094				Twin Tube Nitro-Gas	2	GS19-081T		
	IFP Monotube Shock Adjustable Spring Seat Height X = 167mm / 6.56"	2	IMS19-50094				IFP Monotube Shock	2	IMS19-50081T		
	X - Centre of Eye to Spring Seat						Monotube Remote Reservoir (3-Way Adjustable) Adjustable Spring Seat Height X = 167mm / 6.56"	2	MRA19-A081T		
	X - Centre of Eye to Spring Seat										
SHOCK ABSORBER BRACKET						SPRING & SHACKLE BUSH KIT					
	Recommended For Optimal Remote Reservoir Positioning And Fitment	1	RM19-002				Kit Contains: 2 x PB19-1523 4 x PB19-1524 4 x PB19-1525	1	PB19-1104K		
	Only For Use With MRA19-A094										
STRUT TOP CAP						U-BOLT KIT					
	Strut Cap	2	SC19-010				Kit Contains: 2 x UB21-466	2	UB21-466K		
SWAYBAR LINK						SHACKLE KIT					
	Must Fit With Dobinsons Shock Absorbers	2	SE19-570				Greasable: Fit in Pairs	2	SK19-058		
SHOCK ABSORBER BRACKET						SHACKLE PIN					
	Recommended For Optimal Remote Reservoir Positioning And Fitment	1	RM19-002				Greasable: Fit in Pairs	2	SP59-060		
	Only For Use With MRA19-A094					TAILSHAFT SPACER KIT					
	Only For Use With MRA19-A094						Tailshaft Centre Bearing Spacer Kit	1	WA19-526K		
	Only For Use With MRA19-A094						Helps to Reduce Driveline Vibration in Lifted Vehicles				