

4x4

HOLDEN - GM - ISUZU




























HOLD-60



TYPE: Colorado RG
 MODEL: RG - GM 1700,
 MMU 142/143/145/147/148
 YEAR: 05/2012 on
 DETAIL: 2.8L Turbo Diesel, Single Cab / Dual Cab



This vehicle has been issued with a recall notice to change the Coil Spring Stepped Isolator. Take care when ordering Coil Springs or Shock Absorbers.

FRONT		QTY	PART NUMBER	PRICE	REAR		QTY	PART NUMBER	PRICE
COIL SPRING					LEAF SPRING				
For vehicles with the Flat Type Upper Coil Isolator					3 + 3 Leaves Medium Duty Raised Height (40mm Lift) Up to 100Kg Constant Load				
	Linear Rate Standard Height (10mm Lift) 50-80Kg	1	C59-134	B		2	L21-140-R		
	Linear Rate Raised Height (40mm Lift)	1	C59-296	B		2	L21-141-R		
	Linear Rate Raised Height (40mm Lift) 40-70Kg	1	C59-300	B		2	L21-142-R		
	Linear Rate Raised Height (40mm Lift) 80-100Kg	1	C59-350	B		2	L21-182-RP		
Suits vehicles with the Coil Spring Stepped Isolator fitted					2 + 1 Leaves (Parabolic) Raised Height (50mm Lift) Up to 70Kg Constant Load Comfort Option				
	Linear Rate Standard Height (10mm Lift) 50-100Kg	1	C21-382	B	SHOCK ABSORBER				
	Linear Rate Raised Height (40mm Lift) Up to 40Kg	1	C21-384	B		2	GS43-801		
	Linear Rate Raised Height (40mm Lift) 50-80Kg	1	C21-386	B		2	IMS21-50471		
	Linear Rate Raised Height (40mm Lift) 80-100Kg	1	C21-388	B		2	MRA43-A801		
SHOCK ABSORBER					SPRING & SHACKLE BUSH KIT				
	Twin Tube Nitro-Gas	2	GS21-470			1	PB21-1105K		
	IFP Monotube Shock Adjustable Spring Seat Height X = 190mm / 7.48"	2	IMS21-50470		Kit Contains: 2 x PB59-1503 (F) 4 x PB59-1530 (R) 4 x PB59-1532 (C)				
X - Centre of Eye to Spring Seat					U-BOLT KIT				
	Monotube Remote Reservoir (3-Way Adjustable) Adjustable Spring Seat Height X = 190mm / 7.48"	2	MRA21-A470			2	UB59-453-2K		
X - Centre of Eye to Spring Seat						2	UB59-437K		
BUMP STOP						2	UB59-437K		
	Replacement Bump Stop Progressive Adjustable 0-20mm Extension	2	BS59-560			2	UB59-437K		
Replaces Original Bump Stop. If Exceeding Listed Spring Seat Heights This MUST Be Used To Prevent Coil Bind.					SHACKLE KIT				
STRUT TOP CAP						2	SK21-059		
	Strut Top Cap	2	SC59-002		SHACKLE PIN				
Can only be used with C59-134 & C59-296						2	SP59-060		

Torsion Bars: Sold in Pairs.
 Coil Springs: Sold in Pairs - Letter Indicates Price Code (A), (B), (C) etc.

*Raised Height Measurements are Listed as a Guide Only.
 ‡All prices are in AUD and subject to change without notice.

FEB21 Rev 0