

4x4
























MAZDA

MAZ-54



TYPE: BT-50
 MODEL: Series II - UP/UR
 YEAR: 10/2011 on
 DETAIL: 4x4 3.2L Pickup/Well Back/Tray Back,
 Also Suits 4x2 Highrider



FRONT			QTY	PART NUMBER	PRICE	REAR			QTY	PART NUMBER	PRICE
COIL SPRING						LEAF SPRING					
4x2 High Rider											
	Linear Rate Raised Height (40mm Lift)	1	C19-420		B		3 + 3 Leaves Medium Duty Raised Height (40mm Lift) Up to 100Kg Constant Load	2	L19-131-R		
	Linear Rate Raised Height (40mm Lift) Comfort Option (Reduced Rate) 50-90Kg	1	C19-428		B		4 + 3 Leaves Heavy Duty Raised Height (40mm Lift) 280Kg Constant Load (Recommended)	2	L19-132-R		
	Linear Rate Raised Height (40mm Lift) 50-90Kg	1	C19-422		B		5 + 3 Leaves Super Heavy Duty Raised Height (40mm Lift) 500Kg Constant Load	2	L19-133-R		
4x4											
	Linear Rate Raised Height (35mm Lift) Comfort Option (Reduced Rate) 50-90Kg	1	C19-428		B		3 + 1 Leaves (Parabolic) Raised Height (50mm Lift) 150Kg Constant Load Comfort Option	2	L19-135-RP		
	Linear Rate Raised Height (40mm Lift)	1	C19-422		B		3 + 1 Leaves (Parabolic) Raised Height (60mm Lift)	2	L19-135-RP		
	Linear Rate Raised Height (40mm Lift) 50-90Kg	1	C19-424		B						
	Linear Rate Raised Height (55mm Lift)	1	C19-424		B						
	Linear Rate Raised Height (55mm Lift) 50-100Kg	1	C19-474		B						
SHOCK ABSORBER						SHOCK ABSORBER					
	Twin Tube Nitro-Gas	2	GS19-092				Twin Tube Nitro-Gas	2	GS19-081T		
	IFP Monotube Shock Adjustable Spring Seat Height X = 190mm / 7.48"	2	IMS19-50092				IFP Monotube Shock	2	IMS19-50081T		
	X - Centre of Eye to Spring Seat										
	Monotube Remote Reservoir (3-Way Adjustable) Adjustable Spring Seat Height X = 190mm / 7.48"	2	MRA19-A092				Monotube Remote Reservoir (3-Way Adjustable)	2	MRA19-A081T		
	X - Centre of Eye to Spring Seat										
Includes Vehicle Specific Bracket. If Vehicle Specific Bracket Does Not Work, Use RM80-005 Universal Bracket											
SHOCK ABSORBER BRACKET						SPRING & SHACKLE BUSH KIT					
Recommended For Optimal Remote Reservoir Positioning And Fitment						Kit Contains: 2 x PB19-1523 (F) 4 x PB19-1524 (R) 4 x PB19-1525 (C)					
1 RM19-002						1 PB19-1104K					
Only For Use With MR19-50092											
BUMP STOP						U-BOLT KIT					
Replacement Bump Stop Progressive Adjustable 0-25mm Extension						Kit Contains: 2 x UB21-466					
2 BS59-560						2 UB21-466K					
Replaces Original Bump Stop. If Exceeding Listed Spring Seat Heights This MUST Be Used To Prevent Coil Bind.											
CONTROL ARM						SHACKLE KIT					
Upper Control Arm											
	(Pair) 3° Castor Built In Rubber Bushes Ball Joint Not Included	1	UCA19-004K			Greasable: Fit in Pairs					
Must Fit When Raising Vehicle Above 50mm To Allow For Improved Caster Angle Alignment						2 SK19-058					
STRUT TOP CAP						SHACKLE PIN					
	Strut Top Cap	2	SC19-009				Greasable: Fit in Pairs	2	SP59-060		
						TAILSHAFT SPACER KIT					
						Tailshaft Centre Bearing Spacer Kit					
						1 WA19-526K					
						Helps to Reduce Driveline Vibration in Lifted Vehicles					

Torsion Bars: Sold in Pairs.
 Coil Springs: Sold in Pairs - Letter Indicates Price Code (A), (B), (C) etc.

*Raised Height Measurements are Listed as a Guide Only.
 ‡All prices are in AUD and subject to change without notice. FEB21 Rev 0